



Lodge 6x6

6 x 6 (5,823 x 5,823) - IE10080040

Basement size is shown in brackets

Fay with double roof construction - IE10080041

- Wall thickness 44 mm T&G;
- Double grooved interlock;
- Wall boards are flat faced with softly rounded edges;
- The corbel of the roof around the whole house;
- Large canopy - 1 m;
- Veranda with canopy 1,9 m;
- Double Glazed windows and doors;
- The doors and windows can be supplied either left, or right-hand;
- The cabin includes the roof and floor;
- Windows can be switched for ventilation.

Living area 29 m²

Possible furnishing: 2 Bedrooms, WC/Bath. Kitchen, hall.

Double roof supplied as optional extras.

Shutters and bitumen shingles are supplied as optional extras



(44mm)

Royal 6x6

6 x 6 (5,823 x 5,823) - IE10080060

Basement size is shown in brackets

- Wall thickness 44-50-44 mm;
- Double grooved interlock;
- Wall boards are flat faced with softly rounded edges;
- The corbel of the roof around the whole house;
- Large canopy - 1 m;
- Veranda with canopy 1,9 m;
- Double Glazed windows and doors;
- The doors and windows can be supplied either left, or right-hand;
- The cabin includes the floor and double roof construction;
- Windows can be switched for ventilation.

Living area 27 m²

Possible furnishing: 2 Bedrooms, WC/Bath. Kitchen, hall.

Shutters and bitumen shingles are supplied as optional extras



double wall
44-50-44